

Tumble dryer

T4300LE

Features and benefits

- Heat pump Tumble Dryer
- Low energy consumption: 0.22 kWh/kg load
- Exhaust duct not needed
- Reversing drum
- Residual moisture control – RMC
- Large door opening for easy loading and unloading
- Anti-wrinkle function
- Built-in service program

Main options

- Stainless steel drum



Main specifications		T4300LE	
Rated capacity, filling factor 1:22/1:30/1:50	kg	13.6/10/6	
Drum volume	litre	300	
Drum diameter	mm	760	
Heat pump effect	kW	3	
Consumption data*			
Status at start		Warm	Cold
Drying time	min	62/46/31	73/54/38
Energy consumption	kWh	2.76/2.01/1.36	3.01/2.24/1.54
Energy/Water evaporation	kWh/l	0.40/0.40/0.44	0.44/0.44/0.50
Energy/Load of linen	kWh/kg	0.20/0.20/0.23	0.22/0.22/0.26

* At rated capacity 100% cotton load at 50% initial moisture dried to 0%.

Certified in accordance with ISO 9001 and ISO 14001 and approved IP X4.

Electrical connections		T4300LE	
Heating Voltage			
400-415V 3NAC 50 Hz	kW(A)	3 (10)	
230-240V 3AC 50 Hz	kW(A)	3 (16)	
Condense connection			
Drain diameter	∅	25	
Sound levels			
Airborne sound level	dB(A)	<70	
Heat emission			
% of installed power, max		15	
Shipping data			
Cabinet, net, kg		120	
Heat pump unit, net, kg		150	
total net, kg		270	
Dimensions in mm			
A Width	790		
B Depth	1284		
C Height	1663		
D	935		
E	740		
F	2024		
G	100		
H	270		
J	895		
1 Door opening ∅ 580 mm	3 Electrical connection		
2 Control panel	4 Condense outlet		

