

Laundry Press – Air operated collar and cuff FPA6-WC



Features and benefits

- High temperature polished head, dries the fabric and gives it a flat finish
- High pressure, achieves an excellent finish
- Adjustable pressure regulator, for pressing different fabrics
- Air operated, reduces operator fatigue
- Safety two button closing, improves operator safety
- Padded buck, reduces impressions
- Adjustable release timer, simplifies the operation and ensures consistent results

Main options

- Facilities that simplify the installation
 - Integral air compressor
 - Integral steam boiler

Electrical connections		Standard	Built-in boiler	Built-in air comp.
Voltage, external boiler				
208-240V 1 AC 50/60 Hz	kW	0.2		1.1
Voltage, internal boiler				
208-240V 3 AC 50/60 Hz	kW	-	alt. 8.4	-
400-415V 3N AC 50/60 Hz	kW	-	10.4	-
		-	12.4	-
		-	15.4	-
		-	18.4	-
Steam, air and vacuum connection				
Steam	DN	15	-	15
Rec. steam pressure	kPa	600	-	600
Steam consumption	kg/h	12-13	-	12-13
Condensate	DN	15	15	15
Compressed air	DN	10	10	-
Rec. air pressure	kPa	700	700	-
Air consumption	l/min	50	50	50
Boiler drain (internal boiler)	DN	-	15	-
Shipping data				
	net, kg	300	300	300
	crated, kg	360	360	360
	boxed, kg	440	440	440
Dimensions in mm				
A	Width	970	970	970
B	Depth	1135	1135	1135
C	Height	1220	1220	1220
D		1530	1530	1530
E		1070	1070	1070
F		780	780	780
G		445	445	445
H		190	190	190
I		150	150	150
K		505	505	505
L		300	300	300
1	Control panel	5	Air connection	
2	Electrical connection	6	Boiler drain (internal boiler)	
3	Steam connection	7	Water supply (internal boiler)	
4	Condensate			

