



# Tumble dryer

## T5130, T5130C

### Features and benefits

- **Compass Pro® microprocessor offers:**
  - Large display and one control knob for easy program selection
  - Language selection
  - Quick start and option buttons for frequently used programs
  - Drying program packages optimized for Economy, Care and Time
  - Service program for adjustment of parameters
  - USB connection
- Residual Moisture Control for an accurate drying result and a low energy consumption
- Reversing drum for less tangling of large items
- Stainless steel drum
- Reversible door hanging for a convenient laundry flow
- Easy access to vital parts from the top and rear for simple servicing
- The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption



*Images shown are a representation of the product only and variations may occur.*

### Main options

- Stainless steel front
- Connection to booking- /payment- system or coin meter
- Stacking frame for mounting T5130 on top of W555H
- Stainless steel base frame
- Integrated condense system

| Main specifications               |                     |       | T5130     | T5130C |
|-----------------------------------|---------------------|-------|-----------|--------|
| Rated capacity,                   | filling factor 1:22 | kg/lb | 6/13      | 6/13   |
| Drum volume                       |                     | litre | 130       | 130    |
| Drum diameter                     |                     | mm    | 575       | 575    |
| Heating alternatives              |                     |       |           |        |
| electric                          |                     | kW    | 5.1 / 3.2 | 3.0    |
| <b>Consumption data*</b>          |                     |       |           |        |
| Total time full load              |                     | min   | 32        | 55     |
| Energy consumption full load      |                     | kWh   | 2.78      | 2.96   |
| Evaporation                       |                     | g/min | 92.8      | 48     |
| Energy kWh/litre water evaporated |                     | kWh/l | 0.94      | 1.00   |

\* At rated capacity 100% cotton load at 50% initial moisture dried to 0%.



| Electrical connections |               |       |                  |                |                    |
|------------------------|---------------|-------|------------------|----------------|--------------------|
| Heating alternative    | Main voltage  |       | Heating power kW | Total power kW | Recommended fuse A |
|                        |               | Hz    |                  |                |                    |
| Electric heated T5130  | 220-230V 1 ~  | 50/60 | 3.1              | 3.3            | 16                 |
|                        | 240V 1 ~      | 50/60 | 3.2              | 3.5            | 16                 |
|                        | 220-230V 3 ~  | 50/60 | 3.1              | 3.3            | 16                 |
|                        | 240V 3 ~      | 50/60 | 3.2              | 3.5            | 16                 |
|                        | 220-230V 3 ~  | 50/60 | 4.9              | 5.1            | 16                 |
|                        | 240V 3 ~      | 50/60 | 5.1              | 5.4            | 16                 |
|                        | 380-400V 3 ~  | 50/60 | 4.9              | 5.1            | 10                 |
|                        | 415V 3 ~      | 50/60 | 5.1              | 5.3            | 10                 |
|                        | 440V 3 ~      | 60    | 5.1              | 5.4            | 10                 |
|                        | 480V 3 ~      | 60    | 5.1              | 5.3            | 10                 |
| T5130C                 | 380-400V 3N ~ | 50/60 | 4.9              | 5.1            | 10                 |
|                        | 440V 3 ~      | 60    | 3.0              | 3.4            | 10                 |
|                        | 380-400V 3N ~ | 50/60 | 3.0              | 3.3            | 10                 |
|                        | 220-230V 3 ~  | 50/60 | 2.9              | 3.3            | 10                 |

| Connections                                       |            | T5130                 | T5130C |
|---|------------|-----------------------|--------|
| Air outlet  | mm         | ø 100                 | -      |
| Maximum air flow                                  | m³/h       | 240                   | -      |
| Condensate  |            | -                     | 1/2"   |
| Maximum static back pressure                      | Pa         | 80                    | -      |
| Sound levels                                      |            |                       |        |
| Airborne sound level                              | dB(A)      | <70                   | <70    |
| Heat emission                                     |            |                       |        |
| % of installed power, max                         |            | 15                    | 15     |
| Shipping data                                     |            |                       |        |
| Shipping volume                                   | net, kg    | 54                    | 57     |
|   | crated, kg | 67                    | 70     |
|   | boxed, kg  | 101                   | 101    |
|   | net, m³    | 0.52                  | 0.52   |
| crated, m³  | 0.63       | 0.63                  |        |
| Accessories                                       |            |                       |        |
| Stacking frame for mounting T5130 on top of W555H |            | x                     | x      |
| Stainless steel base frame                        |            | x                     | x      |
| Dimensions in mm                                  |            |                       |        |
| A Width   |            | 595                   | 595    |
| B Depth   |            | 735                   | 735    |
| C Height  |            | 850                   | 850    |
| D   |            | 80                    | 80     |
| E   |            | 80                    | 80     |
| F   |            | 100                   | 100    |
| G   |            | 200                   | 200    |
| H   |            | 235                   | 235    |
| I   |            | 115                   | 115    |
| J   |            | 300                   | 300    |
| K   |            | 70                    | 70     |
| 1 Door opening ø 370 mm                           |            | 3 Exhaust connection  |        |
| 2 Electrical connection                           |            | 4 Condense connection |        |

\* Other voltages available, see installation manual.

